



# UT132 SERIES

## Palm Size Digital Multimeters

UT132C / UT132D



UL61010-1  
EN61010-1  
EN61010-2-030  
EN61326-1



■ UT132C



■ UT132D

### SPECIFICATIONS



Specifications	Range	Best Accuracy	
Model		UT132C	UT132D
DC Voltage(V)	200mV/ 2000mV/ 20V/ 200V/ 600V	±(0.5%+2)	±(0.5%+2)
AC Voltage(V)	200V/ 600V	±(1.2%+3)	±(1.2%+3)
DC Current(A)	2000µA/ 20mA/ 200mA/ 10A	±(1%+2)	
	2000µA/ 200mA/ 10A		±(1%+2)
Resistance(Ω)	200Ω/2000Ω/20kΩ/200kΩ/2000kΩ/20MΩ	±(0.8%+5)	
	200Ω/ 2000Ω/ 20kΩ/ 200kΩ/ 20MΩ		±(0.8%+5)
Capacitance (F)	20nF/ 2000nF/ 200µF		±(4%+3)
Temperature (°C)	-40 °C ~ 1000°C	±(1.0%+3)	
Features			
Display Count		2000	2000
Manual Range		✓	✓
Diode		✓	✓
Continuity Buzzer		✓	✓
Low Battery Indication		✓	✓
Data Hold		✓	✓
Input Impedance for DCV	Around 10MΩ	✓	✓

### GENERAL CHARACTERISTICS

Power	9V Battery(6F22)
LCD Size	49mm×18mm
Product Color	Red and Grey
Product Net Weight	200 g
Product Size	72mm×137mm×35mm
Standard Accessories	UT132C-Battery, Test Lead, Point Contact Temperature Probe
	UT132D-Battery, Test Lead,
Standard Individual Packing	Gift Box, English Manual
Standard Quantity Per Carton	66 PCs
Standard Carton Measurement	595mm × 360mm × 420mm (0.09CBM Per Standard Carton)
Standard Carton Gross Weight	25.7 Kg