

Models	UT39A+	UT39C+	UT39E+	UT136B+	UT136C+	UT890C	UT890D+	UT89X	UT89XD	UT89XE
Page	057	057	057	070	070	076	076	061	061	061
DC voltage (V)	1000V	1000V	1000V	1000V	1000V	1000V	1000V	1000V	1000V	1000V
AC voltage (V)	750V	750V	1000V	1000V	1000V	750V	750V	1000V	1000V	1000V
DC current (A)	10A	10A	20A	10A	10A	20A	20A	20A	20A	20A
AC current (A)	10A	10A	20A	10A	10A	20A	20A	20A	20A	20A
Resistance (Ω)	200MΩ	40MΩ	200MΩ	40MΩ	40MΩ	60MΩ	60MΩ	60MΩ	60MΩ	200MΩ
Capacitance (F)	10mF	10mF	2000μF	40mF	40mF	100mF	100mF	100mF	100mF	200mF
Frequency (Hz)		1MHz	2MHz	40MHz	40MHz	10MHz	10MHz	10MHz	10MHz	60MHz
Temperature (°C)		-40°C ~1000°C	-40°C ~1000°C		-40°C ~1000°C	-40°C ~1000°C		-40°C ~1000°C		-40°C ~1000°C
Features										
Display count	4000	4000	20000	4000	4000	6000	6000	6000	6000	20000
Diode/continuity	●	●	●	●	●	●	●	●	●	●
Low battery indication	●	●	●	●	●	●	●	●	●	●
Data hold	●	●	●	●	●	●	●	●	●	●
Auto power off	●	●	●	●	●	●	●	●	●	●
LCD backlight	●	●	●	●	●	●	●	●	●	●
Duty cycle								●	●	
Relative mode	●	●	●			●	●	●	●	●
NCV		●	●	●		●	●	●	●	
Auto range				●	●					
Trnsistor (hFE)	●	●	●	●	●	●	●	●	●	
Conductance (nS)			●							●
Live test							●	●		
LED test									●	
Max/Min						●	●			●
True RMS						●	●	●	●	●
Safety Features										
Drop test	1m	1m	1m	1m	1m	1m	1m	1m	1m	1m
Safety rating	CAT II 1000V/CAT III 600V									



UT136C+



Specifications	Range	UT136B+	UT136C+
DC voltage (V)	1000V	$\pm(0.7\%+3)$	$\pm(0.7\%+3)$
AC voltage (V)	1000V	$\pm(1\%+3)$	$\pm(1\%+3)$
DC current (A)	10A	$\pm(1\%+3)$	$\pm(1\%+3)$
AC current (A)	10A	$\pm(1.2\%+5)$	$\pm(1.2\%+5)$
Resistance (Ω)	40M Ω	$\pm(0.8\%+2)$	$\pm(0.8\%+2)$
Capacitance (F)	40mF	$\pm(3\%+5)$	$\pm(3\%+5)$
Frequency (Hz)	400Hz~40MHz	$\pm(0.1\%+4)$	$\pm(0.1\%+4)$
Temperature ($^{\circ}\text{C}$)	-40~1000 $^{\circ}\text{C}$		$\pm(1\%+3)$
Temperature ($^{\circ}\text{F}$)	-40~1832 $^{\circ}\text{F}$		$\pm(1.5\%+5)$
Display count		4000	4000
NCV		v	
Category ratings	CAT II 1000V, CAT III 600V		

Features

Equipped with 3mm protective sleeve	Measures up to 1000V and 10A AC/DC current
Quick sampling rate, up to 4 times/s	Large LCD display
Transistor measurement	Quick capacitor measurement (measures 1mF in 4 seconds)
Overload alarm	Diode/continuity buzzer
LCD backlight	Data hold/Auto power off
2m drop proof	Low power consumption and auto power saving function

Characteristics

Standard accessories	Batteries, test leads, temperature probe (UT136C+), English manual
Power	1.5V battery (R6) x 2
Display	56.5 x 36mm
Product size	175 x 83 x 53mm
Product net weight	330g
Standard individual packing	Gift Box
Standard quantity per carton	30pcs
Standard carton measurement	390 x 355 x 355mm
Standard carton gross weight	14.8kg