




Models		UT682	UT682D	UT683KIT
Page		160	160	161
				
Wire types		LAN cable\telephone line \coaxial cable\electric wire	Telephone line\twisted-pair \electric wire	LAN cable\telephone line \coaxial cable\electric wire
Transmitter	Port flashing			●
	Wire tracking	●	●	●
	Line alignment	●		●
	Continuity	●	●	●
	Polarity test	●	●	●
	Ringing signal test		●	●
	Low battery indication	●	●	●
	Input protection	●	●	●
	Auto power off			●
	Power	9V battery	9V battery	1050mAh rechargeable lithium battery
Receiver	Wire tracking	●	●	●
	NCV function			●
	Flashlight			●
	Headset jack	●	●	●
	Low battery indication	●	●	●
	Auto power off			●
Power	9V battery	9V battery	1050mAh rechargeable lithium battery	
Certificates		CE/UKCA	CE/UKCA	CE/UKCA



UT682 Wire Tracker

UT682D Tone and Probe

UT682 wire tracker consists of a transmitter and a receiver, it is able to track ethernet/telephone/power cables without opening their insulation. UT682 can troubleshoot ethernet cables and is a recommended tool for debugging communication cables and audio/video cables.

Specifications	UT682	UT682D
Certificates	CE, UKCA	
LAN cable/telephone line/coaxial cable/electric wire	√	
Telephone line/twisted-pair/electric wire		√
Indication light for signal strength	√	
Live switchboard wire tracing	√	
Switchboard wire tracing distance	≥100m	
Telephone lines tracking distance	≥3000m	≥3000m
Cables tracking distance	≥320m	
Open and short circuit test	√	
Polarity indication for telephone lines	√	√
Broken wire tracking	√	
Transmitter low battery indication	√	√
Headphone jack for receiver	√	
Line sequence measurement	9 LEDs	
Line sequence measuring speed	Fast and slow selectable	
LAN cable: shielded/unshielded indication	√	

Characteristics	
Standard accessories	9V battery x 2, RJ11 cable (UT682), RJ45 cable (UT682), RJ11 cable with alligator clips (UT682), English manual
Product size	UT682: Transmitter-125 x 48 x 28mm, receiver-195 x 48 x 30mm UT682D: Transmitter-74 x 68 x 28mm, receiver-208 x 47 x 33mm
Product net weight	UT682: Transmitter-125g, receiver-153g; UT682D: Transmitter-150g, Receiver-130g
Standard individual packing	Gift box, carrying bag (UT682)
Standard quantity per carton	20pcs
Standard carton measurement	425mm x 335mm x 290mm
Standard carton gross weight	8.4kg