

| Key Specifications | UT8804E | |
|------------------------------|-------------------------------------|--------------------|
| | Range | Accuracy (90 days) |
| DC voltage (V) | 1000V | ±(0.025%+5) |
| AC voltage (V) | 1000V(45Hz~100kHz) | ±(0.3%+30) |
| DC current (A) | 10A | ±(0.08%+10) |
| AC current (A) | 10A(45Hz~10kHz) | ±(0.6%+20) |
| Capacitance (F) | 60mF | ±(0.05%+2) |
| Conductance (nS) | 60nS | ±(2%+10) |
| Frequency (Hz) | 60MHz | ±(0.01%+5) |
| Duty cycle (%) | 10%~90% (10Hz~2kHz) | ±(1.2%+30) |
| Temperature (°C/°F) | -40°C~1000°C | ±(1%+30) |
| | -40°F~1832°F | ±(1.5%+50) |
| Display count | 59999 | |
| DCV Accuracy | 0.3% | |
| Sampling speed | 2~3rdgs/s | |
| Range | Auto, manual | |
| True RMS | √ | |
| Date display | √ | |
| Frequency response (Hz) | 100kHz | |
| Diode/transistor test | √ | |
| Data storage | 20000 | |
| On-off beep | √ | |
| Data hold | √ | |
| Standard interface | USB Device | |
| Power | 100V/120V/220V/240V ±10%, 47Hz~63Hz | |
| Display | 4.3 inch TFT LCD | |
| Product net weight | 3.7kg | |
| Product size (W×H×D) | 239mm x 109mm x 344mm | |
| Standard quantity per carton | 2pcs | |
| Standard carton size | 380mm x 330mm x 320mm | |
| Standard carton gross weight | 9.5kg | |

| Ordering Information | |
|----------------------|---|
| UT8000E Series | UT8804E: Digital Multimeter (59999, Auto) |
| Standard Accessories | International standard power cord |
| | USB interface cable |
| | Test leads |
| | Simple test lead with alligator |
| | K-type temperature probe |