


PIN	1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16	17	18	19	20
COM	COM			4E	4D	4C	4DP	3E	3D	3C	3DP	2E	2D	2C	2DP	1E	1D	1C	1B	
PIN	21	22	23	24	25	26	27	28	29	30	31	32	33	34	35	36	37	38	39	40
COM	1A	1F	1G	2B	2A	2F	2G	L	3B	3A	3F	3G	4B	4A	4F	4G				COM



NOTES:

1. VIEWING ANGLE: 6:00 O'CLOCK
2. DISPLAY MODE: POSITIVE/TRANSELECTIVE/TN TYPE
3. DRIVING VOLTAGE: 5.0V, STATIC, FREQUENCY: 64HZ
4. OPERATING TEMP.: -10° C TO 60° C
5. STORAGE TEMP.: -40° C TO 80° C
6. CONNECTOR: PIN TYPE

6																					
5																					
4																					
3																					
2																					
1	MODIFY PIN LENGTH	28/09-05	YJH	CHECKED BY		DESIGN BY	YJH/OSH	08/07-05	COMPOSE TYPE:												
VER.	MODIFY	CONTENTS	DATE	DESIGN	APP	BY			TOLERANCES UNLESS OTHERWISE STATED .X ±0.20 ANGLES ±1° ALL DIMENSIONS IN MM UNLESS OTHERWISE STATED CUSTOMER: XMO APPLICATION: <input type="checkbox"/> Instrument <input type="checkbox"/> Medical/look <input type="checkbox"/> Teletype <input type="checkbox"/> Automobile <input type="checkbox"/> Home Appliance <input type="checkbox"/> Air-condition SAMPLE: <input type="checkbox"/> Yes <input checked="" type="checkbox"/> No												
XIAMEN OCULAR LCD DEVICES CO., LTD											SHEET 1 OF 1										