





Models	UT123	UT123T	UT123D	UT125C	UT133A	UT133B	UT60S	UT60EU	UT60BT
Page	067	067	066	068	069	069	052	053	053
DC voltage (V)	600V	600V	600V	600V	600V	600V	1000V	1000V	1000V
AC voltage (V)	600V	600V	600V	600V	600V	600V	1000V	1000V	1000V
DC current (A)			10A	400mA	10A	10A	10A	10A	10A
AC current (A)			10A	400mA	10A		10A	10A	10A
Resistance (Ω)	20MΩ	20MΩ	40MΩ	40MΩ	60MΩ	60MΩ	100MΩ	100MΩ	100MΩ
Capacitance (F)			4000μF	100μF	10mF	10mF	100mF	10mF	10mF
Frequency (Hz)				60kHz	1MHz		10MHz	10MHz	10MHz
Temperature (°C)	-40°C~300°C	-40°C~300°C			-40°C~1000°C		-40°C~1000°C	-40°C~1000°C	-40°C~1000°C
Features									
Display count	4000	4000	4000	4000	6000	6000	9999	9999	9999
Diode/continuity	Continuity	Continuity	●	●	●	●	●	●	●
Low battery indication	●	●	●	●	●	●	●	●	●
Data hold	●	●	●	●	●	●	●	●	●
Auto power off	●	●	●	●	●	●	●	●	●
LCD backlight				●	●	●	●	●	●
Duty cycle				●			●	●	●
Relative mode					●	●	●	●	●
NCV	●	●	●	●	●	●	●	●	●
Auto range	●	●	●	●	●		●	●	●
True RMS			●				●	●	●
Bluetooth/APP									●
Safety Features									
Drop test	1m	1m	1m	1m	1m	1m	1m	1m	1m
Safety rating	CAT III 600V						CAT II 1000V/CAT III 600V		
Certificates		CE/UKCA /cETLus	CE/UKCA	CE/UKCA /cETLus	CE/UKCA /cETLus	CE/UKCA /cETLus	CE/UKCA/cETLus		



UT123D

UT123D smart digital multimeter is designed to automatically identify AC/DC voltage, resistance, diode, and continuity. With the press of one button, all measurement modes can be manually selected including capacitance. The compact design and EBTN display makes it a great tool for home, DIY, and working in dark environments.

LED FUNCTION DESCRIPTIONS				
Functions				
	LED off	Green LED	Yellow LED	Red LED
*NCV		30V~60V	60V~100V	>220VAC
Battery power	LED ON for 2s when power on	Normal (>2.7V)	Low (2.5V~2.7V)	No power (<2.5V)

*NCV voltage values above are tested at contact distance (0cm) from the charged bare wire, it is used for reference only. When meter is at some distance away from test object, NCV indication light may change to the weaker voltage color.

Specifications	Range	Accuracy
Certificates	CE, UKCA	
DC voltage (V)	600V	±(0.5%+3)
AC voltage (V)	600V	±(0.8%+3)
DC Current (A)	10A	±(1%+3)
AC Current (A)	10A	±(1.2%+3)
Resistance (Ω)	40MΩ	±(0.8%+2)
Capacitance (F)	4000μF	±(4%+5)
Category ratings	CAT III 600V	

Features		
True RMS		NCV/Live
Low Battery Indication: ≤2.7V		Data Hold
Acousto-optic indication: NCV/battery power		Auto Power Off

Characteristics	
Standard accessories	English manual
Power	1.5V battery (R03) x 2
Display	44 x 26mm
Product size	130 x 65 x 28mm
Product net weight	130g
Standard individual packing	Gift box
Standard quantity per carton	60pcs
Standard carton measurement	480 x 340 x 325mm
Standard carton gross weight	16.1kg