## Wire Trackers UNI-To

| Models       |                        | UT682  | UT682D  | UT683KIT  |
|--------------|------------------------|--|---|---|
| Page         |                        | 160  | 160   | 161   |
|              |                        |  |   |   |
| Wire types   |                        | LAN cable\telephone line<br>\coaxial cable\electric wire | Telephone line\twisted-pair<br>\electric wire | LAN cable\telephone line \coaxial cable\electric wire |
|              | Port flashing          |  |   | •   |
|              | Wire tracking          | •  | •   | •   |
|              | Line alignment         | •  |   | •   |
| Transmitter  | Continuity             | •  | •   | •   |
|              | Polarity test          | •  | •   | •   |
|              | Ringing signal test    |  | •   | •   |
|              | Low battery indication | •  | •   | •   |
|              | Input protection       | •  | •   | •   |
|              | Auto power off         |  |   | •   |
|              | Power                  | 9V battery   | 9V battery                                    | 1050mAh rechargeable lithium battery                  |
|              | Wire tracking          | •  | •   | •   |
|              | NCV function           |  |   | •   |
|              | Flashlight             |  |   | •   |
| Receiver     | Headset jack           | •  | •   | •   |
|              | Low battery indication | •  | •   | •   |
|              | Auto power off         |  |   | •   |
|              | Power                  | 9V battery   | 9V battery                                    | 1050mAh rechargeable lithium battery                  |
| Certificates |                        | CE/UKCA  | CE/UKCA                                       | CE/UKCA   |



The device is an intelligent wire tracker which consists of the transmitter and receiver, this kit is designed with strong anti-interference ability. The receiver can quickly and accurately locate the target cable. This kit can automatically identify open, short, polarity, and quickly distinguish cable failure.





| Specifications         | Description           |  |
|------------------------|-----------------------|--|
| Certificates           | CE, UKCA              |  |
| Transmitter            |                       |  |
| Port flashing          | V                     |  |
| Wire tracking          | V                     |  |
| Line alignment         | V                     |  |
| Open-short test        | 10kΩ                  |  |
| Polarity test          | √                     |  |
| Operating time         | >8 hours              |  |
| Receiver               |                       |  |
| Wire tracking          | RJ11>3000m; RJ45>100m |  |
| NCV function           | V                     |  |
| Headset jack           | 3.5mm                 |  |
| Low battery indication | V                     |  |
| Operating time         | >5 hours              |  |

| Characteristics              |   |  |  |  |
|------------------------------|---|--|--|--|
| Standard accessories         | USB cable, RJ11 alligator clip test cable, RJ45 test cable, RJ11 test cable, English manual |  |  |  |
| Power                        | 1050mAh rechargeable lithium battery  |  |  |  |
| Product size                 | Transmitter-130 x 51 x 28mm; Receiver-197 x 48 x 34mm                                       |  |  |  |
| Product net weight           | Transmitter: around 95g; Receiver: around 127g  |  |  |  |
| Standard individual packing  | Gift box, carrying bag  |  |  |  |
| Standard quantity per carton | 20pcs   |  |  |  |
| Standard carton measurement  | 480 x 370 x 325mm   |  |  |  |
| Standard carton gross weight | About 10kg  |  |  |  |